

PRODUCT INFORMATION

NAVIGO 6 CO

Description

NAVIGO 6 CO is an alkaline marine crankcase lubricant for low-speed marine two-stroke crosshead diesel engines.

Application

NAVIGO 6 CO is primarily a crankcase lubricant for low-speed marine diesel crosshead engines running on residual fuel. It is also suitable for plain bearings of turbochargers, shaft bearings, stern tube and seals. In addition, the alkalinity is sufficient to neutralize crankcase contaminations or acidic combustion products in a less demanding four-stroke trunk piston diesel engine running on distillate fuel.

Features/Advantages and Benefits

- Excellent thermal and oxidation stability and detergency
 - Excellent deposit control of oil-cooled piston undercrown
 - Clean crankcase
- Extended oil life due to efficient water separating properties
- Rust and corrosion properties
- Good wear protection
- Approved by major engine manufacturers

Typical Characteristics

Grade Name	Pour point °C	Flash point (COC) °C, min	Viscosity at 100°C cSt	SAE	Base number mgKOH/g
NAVIGO 6 CO	-6	220	11.5	30	6

MARINE IN ALL WE DO!

LUKOIL Marine Lubricants DMCC
is Registered & Licensed as a Free Zone
Company under the Rules & Regulations
of DMCCA

JBC 4 Tower, 15th Floor, Unit No. 1506
Jumeirah Lakes Towers
P.O. Box 487718
Dubai, United Arab Emirates

Tel: +971 4 43 00769
Fax: +917 4 797 6800
technical@lukoil.com

Health and Safety

The Safety Data Sheet is available on request and describes the product in terms of safety in use, handling and transport. The product is not classified as dangerous according to the Regulations 1907/2006 and 1272/2008 or the Directive 1999/45/EC. When used as intended, this product does not pose significant health risks. Repeated exposure may cause skin dryness or cracking. In case of skin contact, immediately wash the affected area with plenty of soap and water. Remove contaminated clothes.

Handling and Packaging

The compatibility and miscibility with comparable products from other suppliers have been tested successfully by an independent institute. In order to benefit from full product performance the mixing of lubricants should be limited to a minimum.

The condition of the circulating oil of a low-speed marine two-stroke crosshead diesel engine should be maintained in accordance with the equipment manufacturers' instructions with a centrifugal purifier to remove water or insoluble components.

The product is available in bulk and drums of approximately 205 litres.

Further Information

For further information about LUKOIL Marine Lubricants please contact any representative of LUKOIL Marine Lubricants or visit our website www.lukoilmarine.com.

LUKOIL Marine Lubricants DMCC
October 2015